Physico-Chemical Parameters of Krishna River Water Especially at Jawahar Nettempadu Project

V.Rajasekhar Reddy *

Assistant Professor, Department of Science & Humanities, St Martin's Engineering. College, Secunderabad, 500100, T.S, India

raja.may2019@gmail.com

Abstract

The physico-chemical parameters of Krishna river water was studied in the month of January 2020. Seven samples were collected from different locations. The parameters like pH, EC, TDS, TS, BOD and DO etc. were determined in Water quality Monitoring laboratory, Wanaparthy,JogulambaGadwaldisrict. The results obtained were compared with standards of ICMR and WHO. From the results it was found that the most of the parameters of Krishna river water are within the permissible limit of ICMR and WHO.

Keywords:Krishna river water, Nettempadu Project, Physico-Chemical Properties, Permissible Limits, Quality of Water.

Introduction

Environment is defined as one's surroundings. The global environment consists of atmosphere, the hydrosphere, and the lithosphere, in which life sustaining resources on the earth are contained. Atmosphere is the mixture of gases extending outward from the surface of earth; evolved from element of earth that were gasified during its formation and metamorphosis. The hydrosphere is made up of the oceans, the lakes and streams and the shallow groundwater bodies that interflow with the surface water. The lithosphere is the soil mantle that wraps the core of the earth. The biosphere, a thin shell that encapsulates the earth, is made up of the atmosphere and lithosphere adjacent to the surface of the earth together with the hydrosphere. Life sustaining resources like air, water and food are withdrawn from the biosphere. In a natural state, earth's life forms live in equilibrium with their environment. Humans have the ability to gather resources from beyond their immediate surroundings and process those resources into different more versatile forms. Anthropogenic, a human induced pollutants, have overloaded the system. As early societies were concerned with meeting natural needs, the overloading came relatively late in the course of human interaction with environment. Early human used natural resources to satisfy their needs for air, water, food and shelter. These natural resources were readily available in the biosphere. Water is most important chemical compound for the perpetuation of life on this planet. It is not only essential for lives but also important chemical compound from engineering point of view. Nearly 2/3 portion of this planet is occupied by water. It is present in three physical forms e.

ISSN: 1475-7192

g. Solid, Liquid and gaseous. It has many unique properties. It is the compound which becomes rarer on solidification. It finds extensive use in the field of agriculture, hydroelectric power generation and air conditioning.

Experimental

For quantitative analysis of Krishna River water, various samples were collected from about 47 Km stretch in between Nettempadu and Thatikunta .The water has been collected from epilimnion during day time. Sample method is same as suggested in APHA, Methods for collection and analysis of water samples. Sampling is done at each station in polythene bottles of two-liter capacity. Sampling has been done in the month of January. The samples analyzed thein have been in Water quality Monitoring laboratory. Wanaparthy, JogulambaGadwaldisrict. The analysis is carried out for determination of physico-chemical properties of Krishna River water such as: pH, EC, total hardness, permanent hardness, chloride content, alkalinity, conductivity, temperature, percentage DO, turbidity, total dissolved solid, total suspended solid, sulphate content, Sodium, Potassium, Iron, Manganese, Zinc, Copper etc.

Physicochemical parameters of these samples were determined by using standard procedure.

- 1. **pH:** The pH is determined by Elico, model LI.120 Digital pH meter which gives direct value of pH.
- 2. **Conductivity:**The conductivity is determined by using digital conductivity meter. The Conductivity meter used is Lavibond made Senso Direct Con.200.
- 3. **Turbidity:** It can be determined by using turbidity meter.
- 4. **Total Solid:**Total solid consists of suspended solid & dissolved solid .This is determined by weight difference method. The 50 ml water sample has been taken in evaporating dish. The total water is evaporated. Whatever total solid matter is present gets accumulated at the bottom of the evaporating dish. After cooling the evaporating dish to room temperature it is again weighed. By weight difference method the total solid present in water is determined.
- 5. **Total Dissolved Solid:** The 50 ml of water sample is filtered through ordinary filter paper and water is collected in the evaporating dish of known weight. Further it is heated and water is totally evaporated. Whatever dissolved solid matter is present gets accumulated at the bottom of evaporating dish. The evaporating dish is cooled and weighed. By weight difference method the total dissolved solid is determined.
- 6. **Total Suspended solid:** This can be determined by the weight difference of total solid and total dissolved solid. TSS =TS –TDS.
- 7. **Total Hardness:** The 50 ml water sample is titrated against 0.01M EDTA (Disodium Salt) solution by using EBT as an indicator. The EDTA of Qualigens is used with 98% purity. This gives the total hardness of water.
- 8. **Permanent Hardness:** The 250 ml water sample is boiled to reduce the volume to 100 ml. It is filtered through ordinary filter paper. This results in removal of temporary hardness. The filtrate is diluted to 250 ml with doubly distilled water. Permanent hardness is determined as above. . Now it is possible to evaluate the temporary hardness of the water.

ISSN: 1475-7192

- 9. Alkalinity: The alkalinity of water sample is determined by titrating it against standard acid solution using indicators like phenolphthalein and methyl orange.
- 10. **Chloride content:** The chloride content of water sample is determined by titrating the water sample against 0.02M silver nitrate solution using potassium chromate as an indicator.
- **11. Sulphatecontent :**The sulphate content in the water sample is determined by using nephelometer.
- **12. Metal Ions:**Metal ions are detected by flame photometry and atomic absorption Spectroscopy. The absorption of energy by ground state atoms in the gaseous state forms the basis of atomic absorption spectroscopy.When a quantitative analysis is to be performed, the sample is atomized and the absorption is measured exactly in same condition.
- 13. **Dissolved Oxygen:** The percentage of DO is determined by using Lavibond made Senso Direct Oxi.200.

Results and Discussion

- 1. **pH**:It is found that pH of the river water slightly varies in studied locations.This variation is due to change in alkalinity of water sample. The pH value ranges from 7.5 to 7.8 units.
- 2. Electrical Conductivity: It is found that Electrical conductivity of river water constantly goes on decreasing from Nettempadu up to village Thatikunta. The conductivity varies from 194.5 μ S to 1030 μ S. The constant decrease in conductivity indicates that there must be reduction in number of dissolved inorganic salts. The conductivity of Krishna River water at Thatikunta site is increased. This increase may be due to the effects of various religious activities performed at river site.
- 3. **Total Hardness:** In the present study it is found that hardness of river water is constantly decreasing along with the downstream path of river. The hardness of water depends upon dissolved salts present in water. It is having maximum hardness at the origin of the river. The decrease in hardness is due to the adsorption of common inorganic salts like Calcium Bicarbonate, Magnesium Carbonate present in water. Total Hardness ranges from 30 ppm to 65 ppm. It is having minimum value at Chinonipally and maximum value of 65 ppm at Narsingwadi. In the present study hardness due to magnesium is the maximum at Guddemdoddi site. The increase in hardness may be due to the domestic activities like washing clothes, animals, vehicles etc. done at the river site. If magnesium content exceeds 50 ppm then water is unsuitable for drinking purpose and it may be laxative. Magnesium is generally found in the form of sulphate.
- 4. **Chloride Contents:**The analysis of water samples shows the irregular variation in Chloride content.. The chloride content is within the permissible limit of Indian Standards. Chloride content is minimum at Udgaoni. e3.4 ppm and maximum at Ankali that is 36.9ppm. The high amount of chloride at Nettempadu may be due to local quality of soil.
- 5. **Alkalinity:**In the present study the alkalinity of water is found to be decreasing along with the downstream of the river. But at the last and second last site of our study, an increase

ISSN: 1475-7192

in alkalinity is noted which could be accounted due to the local factors such as religious place, agricultural place etc.

- 6. **Total Solid:**An attempt is made to determine the total solid content of Krishna River water. From the result it is clear that the total solid content decreases along with downstream of River except Gddemdoddi. This decrease may be due to the adsorption of dissolved salts on earth surface. Furthermore this decrease in total solids is also due to the natural purification system of river such as the effect of sunlight and microbial activities going in the riverbed.
- 7. **Dissolved Oxygen:** The maximum concentration of oxygen that can be dissolved in water is function of temperature and therefore dissolved oxygen content of water may vary from place to place and time to time. In India average tropical temperature is 27[°]C. Corresponding to this temperature, average dissolved oxygen saturation concentration is reported to be 8 ppm.. This is the saturation limit at specific temperature, this represents

100% concentration. The percentage of DO is suitable for survival of aquatic life. Percentage D.O. is graphically represented in Fig. No.15.

8. **Dissolved Inorganic Ions:** In the present research work, metal ions have been analyzed by using flame photometry and atomic absorption spectroscopy. These inorganic ions are found to be within the permissible limit for drinking water.

Science of Water:

It is the important chemical compound present on earth which remains in liquid state over long range i. e. 0^0 to 100^0 C. Hence this compound can easily used as the solvent at various temperatures. It is excellent solvent for inorganic chemicals. This is because of its polar nature. It is having bent structure with bond angle 104^0 28'. The molecular structure of water is

Because of polar nature there is force of attraction between any ion and that end of H_2O molecule which is of opposite sign.

ISSN: 1475-7192

This is due to ion dipole force of attraction. The force of attraction between ions and dipolar H_2O molecule forms hydrated ions which are lower in energy than the separate ions and water molecule. Water is the most important inorganic compound which plays vital role in sustaining life on earth and for development of civilization It constitutes about two third of the earth surface. Based on salinity, it can be broadly divided into ocean (97%) and fresh water (3%). Most of the latter are not accessible because about 87% of it is locked in the ice-cap and glacier atmosphere, soil and in the deep underground (Paul and Misra 2004). Pollution parameters have been classified as physical, chemical and biological on the basis of

analytical tests. Physical parameters include PH, temperature, colour, turbidity, conductivity, suspended matter, and dissolved matter. Chemical parameters include inorganic salts, Dissolved Oxygen (DO), Biochemical Oxygen Demand (BOD), Chemical Oxygen Demand (COD), Nitrogen, Alkalinity, Chloride Content, Hardness of water, and different heavy metal ions present in water. Biological parameters include specific diversity, pathogens, and bioassay etc.

The quality of water needs to be evaluated thoroughly to generate base line information for welfare of society. NiranjanBabuet. al.^[1] has explained health problems identified in developing urban areas. It becomes important to determine the quality of water so that the suitability of water for drinking purpose, agriculture purpose and industrial purpose can be evaluated. Vijay Deshpande et al^[2]have classified water based upon its extent of pollution. The quality of particular water is determined by its Physico-Chemical properties. Most of Indian Rivers' water is polluted. The level of harmful element is found to increasing in all rivers. So, an attempt is made to study the physico-chemical parameters of Krishna river water.

In the present study the water of Krishna River at JawaharNetempadu Lift Irrigation Project -GadwalJogulamba district,Telangana has been analyzed.This Project seeks to lift 21.425 TMC of water from Krishna River from the foreshore of Jurala Project and will provide irrigation to about two lakh acres in Dharur and Gadwalmandals of drought-prone and backward areas.

The main objective of study is

1) To evaluate the physico-chemical properties of Krishna river water from Nettempadu to Thatikunta.

2) To compare the results with WHO norms and ICMR norms.

3) To suggest methods of purification if required.

Topographical Study of Area

The Krishna River is the second largest eastward draining, Perennial River in the Peninsular India. The River Krishna drains an area of 258,948 km², which is nearly 8% of the total geo-graphical area of the country. There are about 25 towns within the basin with the population more than hundred thousand. The average annual rainfall in the river basin is about 780 mm. The wet seasons sets in by the middle of June and withdraws by the middle of October. About 90% of the rainfall occurs during the wet season (June-October) and during

ISSN: 1475-7192

the rest of the year (dry season) there is very little rainfall with no regular pattern.. The important land uses include agricultural land use (double crop -35 %; single crop -25 %), forests (15%), waste land (15%) and mixed land use (10%). The predominant soils in the area are sandy loams and loams. The river reach between the monitoring stations is approximately 47 km long with two tributaries joining the river. The sampling station includes nine different locations from Nettempadu. The villages are Guddemdoddi,Relampadu,Sangala,Chinonipally, Nagardoddi, Thatikunta.

Paramete	Nettemp	Guddemd	Relemp	Sanga	Chinonip	Nagardod	Thatik
rs	adu	odi	adu	la	ally	idii	unta
Air Temp.	37.8	37	37.9	38	36.8	36.7	36.7
Water Temp.	31.5	30.8	31.7	31.8	30.3	30.5	30.6
pН	7.6	7.6	7.5	7.6	7.6	7.5	7.5
EC	265	373	194.5	320	230	270	392
TotalHard ness, ppm	45	45	35	41	30	32	36
Ca+2 (ppm)	27	25	20	24	18	19	20
Mg+2 (ppm)	18	20	15	17	12	13	16
Permanent Hardnes,	18	21	14	15	10	11	14
ppm Chloride, ppm	16.4	18.3	23	3.4	4	.12	6.8
Sulphate, ppm	48	63	58	66	60	67	71
Alkalinit, ppm	148	135	132	122	125	101	92
Total Solid, ppm	420	470	50	80	110	100	160
Dissolved Solid, ppm	320	310	30	60	75	60	105
Suspended solid, ppm	100	160	20	20	35	40	55
Dissolved oxygen (%)	18%	21%	18%	19%	24.5%	20%	24.3%
(%) Na, ppm	20	22	21	21	22	21	20
Ka, ppm	20 2.1	22 1.9	2.3	2.3	22	1.8	20 1.8
ix, ppm	2.1	1.7	4.5	2.5	4	1.0	1.0

Table 1: Physico-Chemical Parameters and heavy metal contents of Krishna River at

 Nettempadu Lift Irrigation Project, Telangana State.

ISSN: 1475-7192

Fe, ppm	0.20	0.21	0.24	0.4	0.22	0.09	0.06
Mn, ppm	0	0	0	0	0	0	0
Zn, ppm	22	21	24	25	23	22	32
Cu, ppm	0	0	0	0	0	0	0

Table 2: Comparison of water parameters with WHO standards in summer season

Parameters	WHO Standards	Average
Air Temperature	No guidelines	37.25
Water Temperature	No guidelines	31.04
pН	No guidelines	7.61
EC	2.50 MS / Cm	377.65
Total Hardness	No guidelines	42.4
Ca Hardness	No guidelines	25.8
Mg Hardness	No guidelines	17.6
Permanent Hardness	No guidelines	16.9
Chloride Content	250 ppm	12.572
Sulphate Content	500 ppm	59.1
Alkalinity		141.5
Total Solid	No guidelines	190
Total dissolved Solid	No guidelines	134
Suspended Solid	No guidelines	56
Percentage DO	No guidelines	0.2143
Na	200 ppm	25.7
К		2
Fa	No guidelines	0.351
Mn	0.5 ppm	0
Zn	3 ppm	23.8
Cu	2 ppm	0
EC	2.50 MS / Cm	377.65
Total Hardness	No guidelines	42.4
Ca Hardness	No guidelines	25.8
Mg Hardness	No guidelines	17.6
Permanent Hardness	No guidelines	16.9
Chloride Content	250 ppm	12.572
Sulphate Content	500 ppm	59.1
Alkalinity		141.5

Table 3: Comparative study of some observed parameters with ICMR standard	ls in summer
season.	

Parameters	ICMRdesirable limit	ICMR Max Limit	Average ObservedValue
pН	6 - 8.5	No Relaxn.	7.61

ISSN: 1475-7192

Total hardnes,ppm	300	600	42.4
CaHardness,ppm	75	200	25.8
Mg Hardness,ppm	50		17.6
Chloride ,ppm	200	1000	12.5
Sulphate,ppm	200	400	59.1
Dissolved Solid ,ppm	500	1500-3000	134
Fe,ppm	0.1	1	0.35
Mn,ppm	0.1	0.5	0
Zn,ppm	0.1	5	23.8
Cu,ppm	0.05	1.5	0

Parameters	No of samples	MAX	MIN	Average
Air Temperature	10	38	36.7	37.25
Water Temperature	10	31.8	30.3	31.04
pH	10	7.8	7.5	7.61
EC	10	1030	194.5	377.65
Total hardnes,ppm	10	65	30	42.4
CaHardness,ppm	10	40	18	25.8
Mg Hardness,ppm	10	30	10	17.6
PermentHardnes,ppm	10	28	10	16.9
Chloride ,ppm	10	36.9	0.12	12.572
Sulphate,ppm	10	71	43	59.1
Alkalinity,ppm	10	231	92	141.5
Total Solid ,ppm	10	470	50	190
Dissolved Solid ,ppm	10	320	30	134
Suspended solid,ppm	10	160	20	56
Dissolved				
oxygen,percent.	10	0.245	0.18	0.2143
Na, ppm	10	44	20	25.7
K, ppm	10	2.3	1.8	2
Fe, ppm	10	0.97	0.06	0.351
Mn, ppm	10	0	0	0
Zn, ppm	10	32	20	23.8
Cu, ppm	10	0	0	0

	No	of			Ave.
Parameters	samples	Variance	Std. Dev.	Poission	Dev.
Air Temperature	10	0.282777778	0.50447993	1.272E-07	0.47
Water Temperature	10	0.311555556	0.55817162	1.0945E-05	0.5
pН	10	0.012111111	0.11005049	0.85262487	0.076

ISSN: 1475-7192

EC	10	56858.11389	238.449395	0	133.61
Total hardnes,ppm	10	138.7111111	11.7775681	2.587E-09	9.08
CaHardness,ppm	10	64.8444444	8.05260482	0.00035491	5.92
Mg Hardness,ppm	10	37.15555556	6.09553571	0.03692045	4.52
PermentHardnes, ppm	10	33.65555556	5.80134084	0.0514721	4.68
Chloride, ppm	10	125.5691733	11.2057652	0.29023812	8.8624
Sulphate, ppm	10	82.3222222	9.07315944	0	7.28
Alkalinity, ppm	10	1722.055556	41.4976572	0	29.3
Total Solid, ppm	10	20577.77778	143.449565	0	106
Dissolved Solid, ppm	10	10743.33333	103.650052	0	80.8
Suspended solid, ppm	10	1843.333333	42.934058	3.996E-14	29.6
Dissolved oxygen %	10	0.000672678	0.02593603	1	0.0223
Na, ppm	10	72.23333333	8.49901955	0.00037808	6.58
K, ppm	10	0.033333333	0.18257419	0.99999169	0.14
Fe, ppm	10	0.090343333	0.30057168	1	0.2234
Mn, ppm	10	0	0	1	0
Zn, ppm	10	12.4	3.52136337	0.00122491	2.56
Cu, ppm	10	0	0	1	0

Conclusion

Water quality is a critical factor in well-being of any area. The various parameters studied are within the permissible limits as per WHO and ICMR norms for drinking water (Table No. 2 &3). So the Krishna river water of studied area is imitable for drinking purposes in the studied period. The water is also suitable for culture of aquatic animals in river in the studied period.

Acknowledgements

I am very thankful to Head of the Department, S & H, St. Martin's Engineering College, Dhulapally, Secunderabad, India for providing necessary facilities. And I am also thankful to DGO, Water quality Monitoring laboratory, Wanaparthy, JogulambaGadwal.

References

- 1. P.N. Babu, N.S. Rao, J.P. Rao, P.C. Rao, Indian J. Geol., 20, 37 (1997).
- A. Sargaonkar, V. Deshpande 'Development of an Overall Index of Pollution for Surface Water based on General classification scheme in Indian context', Environmental Monitoring and Assessment 89, 43-67 (2003).
- 3. M. C. Shekhar, Journal of Water Science and Technology
- F. H. Rain, L.L. Thatcher, Methods for Collection and Analysis of Water Samples, U. S. Govt. OfiiceWashigton, USA (1990).
- 5. C.S. Rao, Environmental Pollution Control Engineering 2nd edition, Wiley Eastern Limited (1993).

ISSN: 1475-7192

- 6. M.J. Pelczer, R.D. Reid, E.C.S. Chem, N.R. Kreig, Microbiology, 5thedn, Mc-Graw Hill Publication, New Delhi (1986).
- 7. R.K. Horton, J. Water Poll. Cont. Fed., 37, 300 (1965).
- Jain and Jain, Engineering Chemistry, 15th edn., DhanpatRai Publishing Company New Delhi. (2007).